PJD5122

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH BRILLIANTCOLOR™ TECHNOLOGY

Easy to use, easy to afford

ViewSonic's PJD5122 is a great little projector that offers outstanding value and performance. This SVGA resolution projector supports high definition signals and projects 2500 lumens for clear, bright images in most lighting conditions. At only 5.1 pounds, it is light and compact, making it ideal for the mobile presenter. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5122 is an excellent multifunctional data/ video projector. Eco-mode reduces fan noise for less distraction during important presentations and even extends the lamp life up to 6000 hours*. For increased security a PIN lock feature allows youto set a password to prevent unauthorized use. The PJD5122 is perfect for tabletop, ceiling mounting or taking on the road.



VERSATILE PRESENTATIONS ANYWHERE

> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

> Bright in virtually any setting

Packs 2,500 ANSI lumens in just 5.1 lb, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> Set to Present

With 8 preset picture modes, including whiteboard, blackboard and cinema it is easy to put toghter a great presentation.

> Eco-mode extends lamp life

Extend the life of your lamp up to 6000 hours* and reduce noise output.

> Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.

> 3D DLP Link Ready

Supports up to 120Hz frame rate.













PJD5122



LIGHT, BRIGHT AND PORTABLE PROJECTOR







Optional Accessories

>Replacement lamp	RLC-055
>Universal ceiling mount kit	WMK-005
>Wireless G presentation gateway	WPG-350
>2nd & 3rd year extended warranty	PRJ-EE-05-03

Projection Distance 4:3 Screen		Scree 4:3 Sc	
M	feet	m	Inches
1.2	3.9	0.7~0.8	28.0~31.7
1.5	4.9	09.~1.0	35.2~40.0
1.8	5.9	1.1~1.2	42.3~48.0
2	6.6	1.2~1.3	47.4~53.7
3	9.8	1.8~2.2	70.3~79.7
5	16.4	3.3~3.4	117.6~133.3
11.3	37.1	6.4~7.6	250~300







ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DICDI (1)		OFFI DUNIAN CONTRACTOR OF THE
DISPLAY	Type Resolution	0.55" Digital Micromirror Device (DLP TM) SVGA 800×600 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	30"-300" / 0.89m-3.9m (Diagonal)
	Throw Distance	3.9' - 37.1' / 1.2m - 11.3m
	Throw Ratio	1.86:1-2.04:1
	Lamp	220 watt
	Lamp Life (Normal / Eco Mode)	4000 / 6000* hours
	Brightness	2500 Lumens
	Contrast Ratio	2000:1 (typ), 3000:1 (dynamic)
	Aspect Ratio	4:3 (native) & 16:9
	Color Gamut	4.5 (Hative) & 10.7 85 % NTSC 1931 CIE
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and
	Computer and video	
		576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps
	Eroguanav	HD 720p, 1080i (24fps, 25pfs and 30fps)
COMPATIBILITY	Frequency PC	Fh: 31-100 KHz, Fv: 48-120 Hz VGA to SXGA
COMPANDILITY	Mac	
CONNECTOR		Up to 1600×1200 @ 60Hz (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub 1 × 15-pin mini D-sub
	RGB Output	·
	Component	2 × 15-in mini -D-Sub (shared with RGB)
	Composite Input	1 × RCA jack
S-Video Inp		1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
AUDIO	Control	1×RS-232 (8 Pin Mini-Din)
AUDIO	Speaker	1×5W
DOWED	Amplifier	1×1W
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
CONTROLS	Consumption	280W (Typical) / <1W (Stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock
	020	auto, mode/enter, source
	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoon
		Picture: Preset mode: brightest, standard (Video),daylight, ViewMatc
		(PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness
		BrilliantColor™, color temp., save settings
		Source: Quick auto search
		System setting (Basic): Language , projector position, auto power off, blan
		timer, panel key lock, timer controller, splash screen
		System setting (Advanced): Quick cooling, high altitude mode, DCR, activ
		VGA out, audio settings, menu settings, closed caption, lamp settings
		security setting, reset all settings
		Information: Current system status (source, preset mode, resolution, colo
		system, equivalent lamp hour)
OPERATING	Temperature	32°F-104°F (0°C-40°C)
CONDITIONS	Humidity	10% - 90% (non-condensing)
	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)
NOISE LEVEL	Normal / Eco Mode	32dB / 26dB
DIMENSIONS	Physical	$10.4 \times 3.8 \times 8.86$ (in) / $264 \times 96.4 \times 225$ (mm)
(W x H x D)	Packaging	13.8 × 8.1 × 11.2 (in) / 350 × 205 × 285 (mm)
WEIGHT	Net	5.1 lb (2.3 kg)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NON
		PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTE	ENTS	ViewSonic projector, power cable, VGA cable, remote control with batterie
		lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year
		Express Exchange® service.
		Rev.1.

Sales: (888) 881-8781 · SalesInfo@ViewSonic.com · ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14947-00B-04/10] PJD5111-1